

# Bosch Video Management System v.2

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Enterprise-class Client/Server based video management system
- ▶ System-wide user management, alarm handling, health monitoring, and configuration
- ▶ Full virtual matrix capabilities, including analog monitor support and CCTV keyboard control
- ▶ Superior alarm handling with alarm priorities and selectable user group distribution
- ▶ Advanced user interface concepts for effective and efficient operation

The Bosch Video Management System is a unique enterprise IP video security solution that provides seamless management of digital video, audio, and data across any IP network. It is designed to work with Bosch CCTV products as part of a total video security management system. You can integrate your existing components into one easy-to-manage system, or use our full-line capabilities and benefit from a complete security solution based on cutting-edge technology and years of experience.

The Bosch Video Management System is installed on a Microsoft Windows Operating Systems.

We recommend using Bosch Workstations and Servers. They are fully tested and optimized for Bosch Video Management System.

In addition to the Bosch ST standard terms and conditions of sale, the Bosch Video Management System software is covered by the Bosch VMS Software Maintenance Agreement, which can be found in your online CCTV product catalog.

## System overview

The Bosch Video Management System contains the following software components:

- Central Server software provides management, monitoring, and control of the entire system

- Video Recording Manager (VRM) and Network Video Recorder (NVR) services provide recording and playback management of video, audio, and data
- Configuration Client software provides the user interface for system configuration and management
- Operator Client software provides the user interface for system monitoring and operation

These software components can be run together on a single PC for small systems or on separate PCs and servers for large systems.

Bosch Video Recording Manager (VRM) provides a Distributed Network Video Recorder solution, eliminating the need for dedicated NVRs, and signaling the second generation of IP Network video recording. The VRM provides load balancing and failover for the iSCSI storage and makes it easy to add additional iSCSI storage later on. VRM introduces the concept of a storage virtualization layer. This abstraction layer enables VRM to manage all of the individual disk arrays in the entire system as a single “virtual” common pool of storage, which is intelligently allocated as needed. The usage of multiple client workstations offers great scalability.

## Functions

### Deployment

- Updates of Operator Client and Configuration Client automatically deployed from Central Server
- Supports all Bosch MPEG4 & H.264 encoders, MPEG4 & H.264 IP cameras and IP AutoDome cameras in SD & HD format, decoders, Allegiant, DiBos, Bosch POS/ATM Bridge, and DiBos-compatible ATM Bridge
- Supported HD resolutions: 720p and 1080p

### Configuration

- Automatic discovery of IP devices
- Automatic IP address assignment of IP devices
- Batch firmware updates of IP devices
- Failover NVR configurable to backup Primary NVRs
- Redundant NVR
- Configurable Logical Tree
- Predefined camera sequences
- “Automatic Sequences” created by multiple selection and drag and drop to Image panes
- Four configurable user-event buttons

### User Interface

- Zoomable sitemaps with links, devices, sequences, and Command Scripts
- Sitemaps in DWF format are used. DWF format version 5.0 and 6.0 are supported.
- Up to 4 PC monitors supported per Workstation
- CCTV keyboard support, connected to either Workstation or IP decoder
- Flexible Image panes allow any combination of video window sizes and layouts
- Any live Image pane can be switched to instant playback
- Multiple instant playback Image panes
- Image windows can display live video, instant playback video, text documents, maps, or web pages
- Device states shown by icons, including network-connection loss, video loss, and camera de-adjustment
- Favorites tree can be individually configured per user
- Favorites tree can include complete views with Image pane layouts and camera assignments
- Camera selection by double-click or drag and drop from site maps, Logical Tree, or Favorites Tree
- Decoders can be organized in Analog Monitor Walls
- Control of analog monitors connected to decoders via drag and drop
- Synchronized playback of up to 16 NVR cameras and up to 16 VRM cameras
- Sophisticated multi-camera timeline allows easy, graphical searching of stored video
- Timeline colors indicate recording status – normal recording, alarm recording, motion recording, protected recording, and audio recording (not for cameras managed by a VRM)
- Easy clip selection by dragging hairlines in the timeline
- Selected clips can be exported to DVD, network drives, or USB sticks with a few mouse clicks
- Flexible search works across all NVRs and DVRs connected to the system

- Post-recording motion search allows changes to selected areas of the image to be easily located
- Forensic Search allows the usage of Intelligent Video Analysis (IVA) algorithms on the recorded video
- Two audio listening options – selected channel only, or multiple simultaneous channels
- Audio Intercom functionality
- 4:3 and 16:9 Image panes

### Scheduling

- Up to 10 Recording schedules with Holidays and Exception Days
- Task Schedules with Holidays, Exception Days, and recurring schedule support
- Per camera settings for minimum and maximum recording times
- Per camera, per recording schedule frame rate and quality settings for live, normal recording, motion recording, and alarm recording

### Event Handling

- Event list with device events (e.g. video loss), system events (e.g. disk full), SNMP traps from network devices (e.g., heavy network traffic), subsystem events (e.g. Allegiant alarm), user events (e.g. logon failure), schedule events (e.g. every Tuesday at 10:15), etc.
- Compound events (combining events with Boolean logic)
- Event duplication allowing separate handling
- Event allocation to user groups
- Schedule dependent alarm generation
- Schedule dependent event logging
- Schedule dependent event-generated Command Script invocation

### Alarm Handling

- Alarms can trigger alarm-mode recording for any cameras
- 100 alarm priorities
- Selective auto-popup on alarm
- Alarms displayed in separate alarm window
- Up to 5 Image panes per alarm with live or playback video, sitemaps, documents, or web pages displayed in an “alarm row”, with highest priority alarms on top
- Audio file per alarm
- Workflow with user instructions and user comments, optionally forced before clearing
- Email or SMS notification on alarm
- Alarm display on analog monitor walls
- Alarm auto clear options either time or state dependent

### User Management

- LDAP compatible for integration with enterprise user management systems such as Microsoft Active Directory
- Access to system resources individually controlled per user group
- Logical Tree customized per user group – users only see devices for which they have access
- User group rights for protecting, deleting, exporting, and printing video
- User group rights for Logbook access

- User group priority assignment for PTZ control and Allegiant camera access
- Individual per-camera privileges assignable per user group for live access, playback, audio, meta data display, dome control
- Dual-authorization logon – special privileges and priorities granted when two users log on together

**System Monitoring**

- System-wide health monitoring, including cameras, computers, software, and network equipment
- Network equipment and other third-party devices monitored with SNMP

**Customization and Interfacing**

- Custom Command Scripts can control all system functionality
- Built in Command Script editor supporting C# and Visual Basic .Net
- External software can trigger events and send metadata via “Virtual Inputs”
- Any .Net programming language (C#, JScript, etc.) or COM programming language (C++, Visual Basic, etc.) can be used to trigger Virtual Inputs
- Other systems can control the virtual matrix with Allegiant CCL commands that can be sent via RS232
- Compatible with Bosch Building Integration System
- Compatible with Advantech ADAM-6000 series Digital Input / Output modules

**Parts included**

- The Base Box is delivered with DVD and Quick Start Manual.
- The DVD contains the following items:
  - Installation program that can selectively install all components (Central Server software, Network Video Recorder software, Video Recording Manager software, Configuration Client software, Operator Client software) in all supported languages
  - Configuration Manual (PDF format) in all supported languages (except Arabic)
  - Operator’s Manual (PDF format) in all supported languages (except Arabic)
- Quick Start Manual in English, French, German, Simplified Chinese and Spanish

Licenses are provided as eLicenses via email.

**Technical specifications**

**System Specifications**

Maximum number of workstations simultaneously viewing the same camera	Multicast: 20 Unicast: 5
Supported languages	English, German, Dutch, Italian, Portuguese, French, Spanish, Simplified Chinese, Traditional Chinese, Russian, Hungarian, Japanese, Czech, Danish, Finnish, Greek, Norwegian, Polish, Swedish, Thai, Turkish, Korean, and Arabic

Anti-Virus software must not perform a full-scan. Performance may decrease depending on configuration.

Event reaction time	<1 second, assuming sufficient network bandwidth
Alarm reaction time (incl. 1 live Image pane, 1 instant playback Image pane and 1 map Image pane):	Maximum 2 seconds, assuming sufficient network bandwidth
Bandwidth requirements	Min. 1 Gbps for connections between: Operator Client to Central Server Operator Client to NVR/VRM/DiBos Central Server to NVR/VRM/DiBos

**Required open ports**

**Connection from Central Server and Client Workstations to NVRs:**

Two selectable TCP ports (default 5390, 5391 and 5393)

**Connection to Operator Client Workstations by BVMS SDK:**

One selectable TCP port (default 5394)

**Connection from Central Server to SMTP (for email notifications):**

TCP Port 25

**Connection to Bosch encoders and decoders:**

Control channel: TCP ports 80 and 1756

Network scan: UDP ports 1757 and 1758

Multicast detection: one selectable UDP port (default 1900)

Multicast video transmission:

For each encoder audio or video stream, 1 selectable UDP port

Unicast UDP transmission: UDP ports dynamically assigned in the range from 1024 to 65000

**Connection to DiBos DVRs (uses DCOM):**

TCP Port 135 plus four TCP ports and four UDP ports dynamically assigned in the range from 1025 to 65535

**Central Server Specifications**

Maximum number of sustained events	For highest performance server, e.g. MHW-S380R6-HC: 5,000 events/s at peaks 2,500,000 events/h received 500,000 events/h thereof written to the system log (Logbook)
Logbook	Supported by SQL Server 2008 R2 (32-bit or 64-bit version) 4 GByte Logbook size
Central Server Redundancy	Available with hardware and software solutions upon request. Please contact Bosch Design Engineer for all redundancy solutions.
Maximum number of Task Schedules	200

## NVR Specifications

Maximum number of cameras and data rate per NVR, for advanced performance server, e.g. MHW-S380R6-MC and Bosch DVA-8K,DVA-16K (AV multistream on, rebuild priority low)

Continuous or motion or alarm recording and 4 playback clients with 4 Image panes each:	64 cameras @ 25 IPS / 4 CIF / 2 Mbps
Continuous (1IPS) and motion or alarm recording and 4 playback clients with 4 Image panes each:	Continuous recording: 64 cameras @ 1 IPS / 2 CIF / 1,5 Mbps Motion or alarm: 64 cameras @ 25 IPS / 4 CIF / 2 Mbps
Motion with pre-motion and alarm with pre-alarm recording and 4 playback clients with 4 Image panes each:	Pre-motion / alarm recording: 64 cameras @ 1 IPS / 2 CIF / 1,5 Mbps Motion / alarm: 64 cameras @ 25 IPS / 4 CIF / 2 Mbps
Redundancy	Failover NVR can be assigned to take over for a failed NVR. Multiple Primary NVRs can be assigned to the same Failover NVR. Redundant NVR can be assigned to a Primary NVR.
Maximum number of Primary NVRs serviced by a Failover NVR	2
Maximum number of NVRs per Central Server	2 For higher camera numbers use VRM.
Device compatibility	H.264 encoders and cameras are not supported for NVRs.

## VRM Specifications

Maximum count of VRM servers per Central Server	5
Maximum data rate per iSCSI	Please contact Bosch Design Engineer for iSCSI storage solutions.
Maximum number IP cameras/ encoders channels per Central Server	500
Max. number of playback sessions	32

## Minimum Client Workstation PC Requirements

Operation System	Windows XP Professional, Service Pack 3 (32-bit only) Windows 7 Professional 64 bit versions (required for > 500 cameras)
CPU	Intel Core 2 Duo
RAM	2 GB or greater

Free disk space	500 MB or greater We recommend having minimum 15% free disk space.
Network card	1000Base-T
Display Resolution	Minimum per monitor 1024x768, 1280x1024 or greater recommended
Recommended Graphic Cards	2 monitors, Entry: - MHW-AWGC-ATIV37 - MHW-AWGC-FX380 - MHW-AWGC-FX580 2 monitors, Mid-range: - MHW-AWGC-ATI57 - MHW-AWGC-FX4800 - MHW-AWGC-FX1800 - MHW-AWGC-FX1700 - MHW-AWGC-FX1700 x2 - MHW-AWGC-NVS295 2 monitors, High-end: - MHW-AWGC-FX4800

## Maximum Graphic Cards Specifications

You find detailed information on the maximum number of Image panes and the CPU load for various workstations or servers and graphic cards in the Application Guide "Display performance indication".

## Minimum Central Server PC Requirements

Operation System	Windows 2008 Server (64-bit) required for > 500 cameras Window 2003 Server, Service Pack 2 (32-bit only) For All-in-one systems and maximum 32 IP cameras/ encoders: Windows XP Professional, Service Pack 3 (32-bit only)
CPU	Intel Core 2 Duo
RAM	4 GB or greater
Free disk space	15 GB or greater We recommend having minimum 15% free disk space.
Network card	1000Base-T
Display Resolution	1024x768 or greater

## Minimum NVR Server PC Requirements

Operation System	Windows XP Professional, Service Pack 3 (32-bit only), Windows 2003 Server, Service Pack 2 (32-bit only) Windows 7 and Windows Server 2008 not supported
CPU	Intel Core 2 Duo
RAM	2 GB or greater
Free disk space	500 MB + Video Storage We recommend having minimum 15% free disk space.

Hard disk drives	Minimum: separate partition for video storage Separate drive for video storage recommended
Network card	1000Base-T
Display Resolution	1024x768 or greater

### Minimum VRM Server PC Requirements

Operation System	Windows XP Professional SP3, 32 bit versions, Windows 7 Professional, 32/64 bit versions, Windows Server 2003 R2, Standard Edition with SP2, 32/64 bit versions, Windows Server 2003 R2, Standard Edition, 32/64 bit versions
CPU	3 GHz Intel Pentium 4 or later, 3 GHz Intel Xeon or later recommended
RAM	Minimum 2 GB
Free disk space	500 MB We recommend having minimum 15% free disk space.
Network card	1000Base-T
Display Resolution	1024x768 or greater

### Device Compatibility

Analog Matrix Switch	Bosch Allegiant series, firmware 8.75 or later and Master Control Software version 2.91
CCTV Keyboard	Bosch Intuikey (KBD-Universal or KBD-Digital), firmware version 1.95 or later
Digital I/O	Digital I/O Advantech ADAM-6050, ADAM-6052, ADAM-6060, ADAM-6066
Digital Video Recorder	DiBos, firmware version 8.7 Maximum 50 DiBos recorders per Central Server
USB to Serial adapter	Belkin serial adapter cable F5U103vea
Ethernet to Serial adapter	Comtrol DeviceMaster RTS 4-Port
IP Devices	VIP-X Series encoders and cameras H.264 Series encoders and cameras MPEG-4, H.264 Main Profile, H.264 Baseline Plus are supported (H.264 Baseline and MPEG-2 not supported)

### Ordering information

#### Demoverision - Non Expandable

1 Forensic Search included.  
Order number **MBV-BDEM-23**

#### Lite-32-Edition - Non Expandable

Supports 32 Cameras, 2 Workstations, 1 CCTV Keyboard, 0 DVRs – Non Expandable  
1 Forensic Search included.  
Order number **MBV-BLIT32-23**

#### Lite-64-Edition - Non Expandable

Supports 64 cameras, 4 Workstations, 2 CCTV Keyboards, 0 DVRs – Non Expandable  
2 Forensic Search included.  
Order number **MBV-BLIT64-23**

#### Professional Edition

Supports 8 Cameras, 2 Workstations, 1 CCTV Keyboard, 1 DVR  
All MBV-X\* and MBV-F\* can only be combined with the Professional Edition.  
1 Forensic Search included.  
Order number **MBV-BPRO-23**

#### 1 Channel Expansion

Expansion, order the exact number required.  
For example, if you order 128 units you can use 128 cameras/decoders in your Bosch VMS. Only those cameras need be counted which are shown in the Logical Tree.  
Order number **MBV-XCHAN-23**

#### 1 Workstation Expansion

Expansion, order the exact number required.  
Order number **MBV-XWST-23**

#### 1 DVR Expansion

Expansion, order the exact number required.  
Order number **MBV-XDVR-23**

#### 1 CCTV Keyboard Expansion

Expansion, order the exact number required.  
Order number **MBV-XKBD-23**

#### 1 Failover NVR Expansion

Expansion, order the exact number required.  
Order number **MBV-XFON-23**

#### 1 Redundant NVR Expansion

Expansion, order the exact number required.  
Order number **MBV-XRN-23**

#### 1 Forensic Search Expansion

Expansion, order the exact number required. You need one license per Workstation, not per camera or encoder.  
Order number **MBV-XFOREN-23**

#### Allegiant Matrix Connection

Order number **MBV-FALG-23**

**ATM/POS Connection**

Order number **MBV-FATM-23**

---

**OPC Server Connection**

Order number **MBV-FOPC-23**

---

**Maintenance Lite-32-Edition**

Order number **MBV-MLIT32**

---

**Base Box**

Hard cardboard box including DVD and Quick Start Manual (in English, French, German, Simplified Chinese, and Spanish)

Order number **MBV-BBOX**

---

**Expansion Box**

Paper box including Setup DVD

Order number **MBV-XBOX**

---

**Services**

**Maintenance Lite-32-Edition**

Order number **MBV-MLIT32**

---

**Maintenance Lite-64-Edition**

Order number **MBV-MLIT64**

---

**Maintenance Professional Edition**

Order number **MBV-MPRO**

---

**Maintenance Channel Expansion**

Order number **MBV-MCHAN**

---

**Maintenance Workstation Expansion**

Order number **MBV-MWST**

---

**Maintenance DVR Expansion**

Order number **MBV-MDVR**

---

**Maintenance CCTV Keyboard Expansion**

Order number **MBV-MKBD**

---

**Maintenance Failover NVR Expansion**

Order number **MBV-MFON**

---

**Maintenance Redundant NVR Expansion**

Order number **MBV-MRN**

---

**Maintenance Forensic Search Expansion**

Order number **MBV-MFOREN**

---

**Maintenance Allegiant Matrix Connection**

Order number **MBV-MALG**

---

**Maintenance ATM/POS Connection**

Order number **MBV-MATM**

---

**Maintenance OPC Server Connection**

Order number **MBV-MOPC**

---

**Represented by:**

**Americas:**

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security  
Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

**China:**

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

**America Latina:**

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com