# **SR Megapixel and HD Lenses**

www.boschsecurity.com





- ▶ SR megapixel optical resolution
- ► High-quality optics
- ▶ 1/2.5-inch and 1/2-inch formats
- ▶ Reliable, robust construction
- ► Focal length options

As CCTV cameras can now capture even higher picture resolutions through the use of HD sensor technology and advanced processing, the lenses also need to have an optical resolution that allows the camera to work at its optimal point.

This range of Super Resolution (SR) megapixel lenses is designed to provide improved image resolution and sharpness, and better depth of field while avoiding the diffraction issues which can occur with megapixel sensors.

They provide long and reliable operation with no maintenance. Comprising varifocal and fixed-focus types, the lenses range from wide-angle to telephoto to cover virtually all applications in CCTV observation systems.

### System overview


This series of SR megapixel lenses includes both fixed-focus and varifocal lenses with SR-iris control. They are compact, rugged, and available in 1/2.5-inch and 1/2-inch image formats. The extent of the range means that an installer is always able to select the most appropriate lens for both camera and application. These lenses come with a standard C or CS mount for use with a variety of cameras. The iris control connection is a four-pin standard plug that fits directly

into the camera's iris output. The lenses deliver impressive optical quality due to their mega pixel resolution, contrast reproduction, and coating. The mechanical construction is designed to withstand both frequent iris control operations and the environmental stress of security installations. For flexible, high-quality, reliable lenses that match a HD camera's performance, this series is the ideal solution.

# **Certifications and approvals**

Region	Certification	
Europe	CE	VLG-3V3813-MP
	CE	VLG-2V1803-MP5
	CE	VLG-4V0940-MP5

# Installation/configuration notes



# 4-pin DC-iris connector (front view)

Pin 1: Damping coil Pin 2: Damping coil +
Pin 3: Driving coil + (open)

Pin 4: Driving coil -

# **Technical specifications**

# **Electrical/mechanical**

See comparison table at the end of this datasheet.

#### **Environmental**

Operating Temperature	-10°C to+50°C (+14°F to +122°F)
Storage Temperature	-40°C to +70°C (-40°F to + 158°F)
Operating Humidity	Up to 93% non-condensing
Certification	CE (DC-iris models)

# **Ordering information**

# Varifocal SR Megapixel Lens

1/2.5-inch varifocal IR corrected lens, CS-mount, 9-40 mm, 5 MP, SR-iris Order number **LVF-5005C-S0940** 

# Varifocal SR Megapixel Lens

1/2-inch varifocal lens, C-mount, 3.8-13 mm, 3 MP, SR-iris

Order number LVF-5003N-S3813

# Varifocal SR Megapixel Lens

1/2.5-inch varifocal IR corrected lens, CS-mount, 1.8-3 mm, 5 MP, SR-iris
Order number **LVF-5005C-S1803** 

#### **Megapixel Lenses** LVF-5005C-S0940 Varifocal SR LVF-5003N-S3813 Varifocal SR LVF-5005C-S1803 Varifocal SR Megapixel Lens Megapixel Lens Megapixel Lens Maximum sensor format 1/2.5-inch 1/2.5-inch 1/2-inch Optical resolution 5 Megapixels 5 Megapixels 5 Megapixels 9 – 40 mm 1.8 - 3 mm 3.8 - 13 mm Focal length Iris range F1.5 to close F1.8 to close F1.4 to close Min object distance 0.5 m (1.64 ft) 0.3 m (1 ft) Back focus distance 8.3 mm (0.33 in) 10.6 mm (0.42 in) Weight 63 g (0.134 lb) 80 g (0.18 lb) **Dimensions** Ø 54 mm x 49.31 mm $\emptyset$ 50 mm x 49.3 mm $\emptyset$ 45.7 mm x 64.2 mm Lens mount CS CS С 97 x 72° Wide 30 x 23° Wide 106 x 90° Wide 77 x 62° Tele Angle of view (HxV) 6.9 x 5.2° Tele 28 x 21° Tele 1/3-inch sensor 16:9 30 x 22° Wide 105 x 90° Wide Angle of view (HxV) 7.1 x 5.3° Tele 77 x 62° Tele 1/2.7-inch sensor 16:9 37 x 20° Wide 111 x 95° Wide Angle of view (HxV) 8.6 x 4.8° Tele 84 x 68° Tele Iris control 4-pin, DC control 4-pin, DC control 4-pin, DC control Focus ctrl manual manual manual Zoom ctrl manual manual manual

yes

### Represented by:

IR corrected

Americas: Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 security.sales@us.bosch.com www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

yes

Asia-Pacific: Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2699 apr.securitysystems@bosch.com www.boschsecurity.asia

#### China:

Bosch (Shanghai) Security Systems Ltd. 201 Building, No. 333 Fuquan Road North IBP North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398 www.boschsecurity.com.cn

America Latina:

IR performance (not with IR

illuminator)

Robert Bosch Ltda Security Systems Division Via Anhanguera, Km 98 CEP 13065-900 Campinas, Sao Paulo, Brazil Phone: +55 19 2103 2860 Fax: +55 19 2103 2862 al.securitysystems@bosch.com www.boschsecurity.com